

ENSTO

AVR66.120L/3K

Recess mnt.universal luminaire

Kód AVR66.120L/3K
GTIN 6418677627408
Název Recess mnt.universal luminaire Ensto
AVR66 IP44 LED 20W/830 E PC O
Popis Jono luminaires can be used widely in different lighting systems. Jono series includes a wide range of technical solutions for different needs of lighting. Jono can be used at home, in offices as well as in storages. It is an excellent luminaire in bathrooms and kitchen. It can be used as a ramp luminaire for corridors and staircases as well as in car shelters and garages.

Dodavatel Ensto Lighting Oy

Technické parametry

Dimensions

Weight: 1.6 kg
Length: 1200 mm
Šířka: 87 mm
Dimensions l x w x h: 1200x55x87
Výška: 55 mm

Temperatures

Operating temperature: $\geq 25\text{ }^{\circ}\text{C}$

Electrical values

Power factor (cos f): 0.98
Electronic control gear: true
Voltage: 230 V
Operating voltage: 230V

Materials

Material: Aluminium, Opal polycarbonate

Colors

Color: White

Features

Light source: LED 20W

With light source: Colour scheme 830

Mechanical

Impact strength: IK05

Certificates

Certificates: ENEC, CE

Ratings

Rated voltage: 220 ... 240 V

Degree of protection: IP44

Rated frequency: 50/60 Hz

Power: 20 W

Protection class: I

ETIM 7: EC002892 Ceiling-/wall luminaire

Svítidla info

Luminaire specific information

Control: -

Lamp base: LED-mod

Glow wire rating: 850 °C

Light source qty and power (W): 1x20

Light source (ILCOS): DS

Light source: LED

Optics: Opal diffuser

Installation: Surface

IN-OUT- looping: Continous

Electrical connection, cable size: 5x2,5

Electrical connection, connector type: Pushwire terminal

Colour temperature: 3000 K

Color rendering index: Ra>80

LED-luminaire luminous flux: 1790 lm

Connected load: 20 W

LED-module changeablilty: Yes

Quantity of luminaires for MCB C16: 120

McAdam rate, SDCM: 4

ETIM

ETIM

Colour rendering index CRI: 80-89

With air slots:	false
Nominal voltage:	220 ... 240 V
Suitable for surface mounting:	true
Colour housing:	White
Protection class:	I
With movement sensor:	false
Height/depth:	55 mm
Control gear included:	true
Length:	1200 mm
Material housing:	Aluminium
Light sharing:	Symmetric
Light outlet:	Direct
Suitable for wall mounting:	true
Suitable for built-in mounting:	false
Material cover:	Plastic, opal
Suitable for emergency lighting:	false
Suitable for light line configuration:	true
Voltage type:	AC
Suitable for ceiling mounting:	true
Suitable for suspended mounting:	false
Beam angle:	Open beam/diffuse
With light source:	true
Covering of the luminaire with thermally insulating material possible:	false
Luminaire with limited surface temperature, sign "D":	false
Rated luminous flux acc. IEC 62722-2-1:	1790 lm
Lamp type:	LED exchangeable
Suitable for number of lamps:	1
Width:	87 mm
Type of control gear:	LED operating device current-controlled
Degree of protection (IP):	IP44
Fit for monitor workplace acc. EN 12464-1:	false
Type of grid:	None
Colour temperature:	3000 K
Max. system power:	20 W
Colour of light:	White
With light sensor:	false

Balení

Balení

Unit:	PCS
Size:	1

Pallet package

Unit:	PCS
--------------	-----

Size:

80